




UNITRONIC® BUS SAFETY



Benefits

- For serial transmission of safety-oriented data

Application range

- For fixed installation and highly flexible applications
- For systems such as SafetyBUS p®, based on the well-known CAN bus system

Product features

- The stated bit rates result in the following cable lengths (maximum) for a bus segment:
 - 500 kbit/s = max. 100 m
 - 250 kbit/s = max. 250 m
 - 125 kbit/s = max. 500 m
 - 50 kbit/s = max. 1,000 m

Product Make-up

- Stranded conductor, 3 cores twisted, colour-coded in accordance with DIN 47100 (white, brown, green), copper braiding, halogen-free outer sheath
- UNITRONIC® BUS SAFETY FD P is as per UNITRONIC® BUS SAFETY, but also suitable for highly flexible applications
- Flame-retardant according IEC 60332-1-2

Technical data

- ETIM** 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable
- Certifications**
Version UNITRONIC® BUS SAFETY FC: AWM Style 2464 (80°C 300 V)
- Mutual capacitance**
(800 Hz): max. 45 nF/km
- Peak operating voltage**
(not for power applications) 250 V
- Conductor resistance**
(loop): max. 52 ohm/km
- Minimum bending radius**
Fixed installation:
10 x outer diameter
- Test voltage**
Core/core: 3000 V
Core/core: 1500 V (FD- version)
- Characteristic impedance**
120 ohm
- Temperature range**
UNITRONIC BUS SAFETY:
Fixed installation: -30°C to +80°C
UNITRONIC BUS SAFETY FD P:
Fixed installation -40°C to +80°C
Moved: -30 to +80°C

Article number	Article designation	Number of cores and mm ² per conductor	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
for fixed installation					
2170295	UNITRONIC® BUS SAFETY	3 x 0.75	7.6	49	68
For highly flexible applications (e.g. power chains)					
2170885	UNITRONIC® BUS SAFETY FD P	3 x 0.75	7.8	49	68

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 SafetyBUS p® is a registered trademark of Pilz GmbH & Co.
 Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- FC STRIP stripping tool refer to page 1002