



H1Z2Z2-K

Cross-linked solar cables - type H1Z2Z2-K certified according to EN 50618

Info

- H1Z2Z2-K (code designation according to EN 50618)
- Substitutes previous ÖLFLEX® SOLAR XLR-R



Benefits

- Reduction of flame propagation and of toxic combustion gases in the event of fire
- Robust against mechanical impacts
- For outdoor applications

Application range

- For use in photovoltaic-systems with rated voltage 1500 V DC
- For the cabling between the solar modules and as extension cable between the module strings and the DC/AC inverter
- Gable and flat roof photovoltaic systems
- Photovoltaic plants and solar parks
- Flexible or building-integrated PV systems

Product features

- Flame retardant acc. to IEC 60332-1-2
- Weather/UV-resistant acc. to EN 50618, appendix E

- Ozone-resistant according to EN 50396
- Good notch and abrasion resistance
- Halogen-free according to IEC 60754-1 (amount of halogen acid gas) Corrosiveness of combustion gases according to IEC 60754-2 (degree of acidity)

Norm references / Approvals

- H1Z2Z2-K (code designation according to EN 50618)
- Items with other cross-sections on request

Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation made of cross-linked copolymer
- Colour of core insulation: white
- Outer sheath made of cross-linked copolymer
- Outer sheath colour: black, red or blue

Technical data

	Classification ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Minimum bending radius Fixed installation: 4 x outer diameter
	Nominal voltage AC U_0/U : 1,0/1,0 kV DC U_0/U : 1,5/1,5 kV Max. permissible operating voltage: DC 1,8 kV
	Test voltage AC 6500 V
	Current rating Im compliance with EN 50618, Table A.3
	Temperature range -40°C to +120°C max. conductor temperature based on EN 60216-1 Ambient temperature range according to EN 50618: -40°C to +90°C

Article number	Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
H1Z2Z2-K				
Core insulation: white / Outer sheath: black				
1023552	4.0	5.8	38.4	62
1023553	6.0	6.3	57.6	84
1023554	10.0	7.4	96.0	126
1023555	16.0	8.1	153.6	197
1023590	25.0	10.3	240.0	270
1023591	35.0	11.8	336.0	370
Core insulation: white / Outer sheath: red				
1023572	4.0	5.8	38.4	62
1023573	6.0	6.3	57.6	84
1023574	10.0	7.4	96.0	126
1023575	16.0	8.1	153.6	197
Core insulation: white / Outer sheath: blue				
1023582	4.0	5.8	38.4	62
1023583	6.0	6.3	57.6	84
1023584	10.0	7.4	96.0	126
1023585	16.0	8.1	153.6	197

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: Coil 100 m; Drum (500; 1000) m
Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- EPIC® CRIMPTOOL refer to page [P208769]
- EPIC® SOLAR 4 M refer to page [P171267]
- EPIC® SOLAR 4 F refer to page [P171767]
- KS 20 cable shears refer to page [P1249]