


ÖLFLEX® CRANE 2ST

Cold flexible PVC cable with external steel supporting elements

ÖLFLEX® CRANE 2ST - PVC control cable, with steel supporting elements for movable control panels and consoles, cold flexible, U_0/U : 300/500V

Info

New Product, Follower of
ÖLFLEX® CRANE 2S



UV-resistant



Optimum strain relief



Suitable for outdoor use



Cold-resistant

Benefits

Two steel support elements that are integrated into the outer sheath on opposite sides absorb the tensile forces during operation

Tensile strength of 2100 N per supporting element

Application range

For connecting movable control panels and consoles

As a self-supporting shaft cable; in high rack systems

Suitable for outdoor applications

Do not use for lift applications!

The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

Last Update (19.07.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16

ÖLFLEX® CRANE 2ST

Product features

Flame-retardant according IEC 60332-1-2
Flexible at low temperatures

Norm references / Approvals

Based on VDE 0250

Product Make-up

Conductor made of bare copper wires
Special PVC-based core insulation
Special textile wrapping to improve sliding movement between the sheath and cores
Special PVC-based outer sheath, black
Opposing, integrated steel supporting elements

Technical Data

Classification ETIM 5:	ETIM 5.0 Class-ID: EC000104 ETIM 5.0 Class-Description: Control cable
Classification ETIM 6:	ETIM 6.0 Class-ID: EC000104 ETIM 6.0 Class-Description: Control cable
Core identification code:	Black with white numbers acc. to VDE 0293-1
Conductor stranding:	Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
Minimum bending radius:	Flexible use: 20 x outer diameter
Nominal voltage:	U0/U: 300/500 V
Test voltage:	4000 V
Protective conductor:	G = with GN-YE protective conductor X = without protective conductor
Temperature range:	Flexible use: -15°C to +70°C

Note

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil \leq 30 kg or \leq 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs and graphics are not to scale and do not represent detailed images of the respective products.

Prices are net prices without VAT and surcharges. Sale to business customers only.

ÖLFLEX® CRANE 2ST

Article number	Number of cores and mm ² per conductor	Cable Ø (mm)	Distance between strain wires (mm)	Copper index (kg/km)	Weight (kg/km)
2027503	8.0 G 1.5	13.6	19	115	430
2027504	12.0 G 1.5	15.5	21	172.8	510
2027505	20.0 G 1.5	20	25	288	720

Last Update (19.07.2018)

©2018 Lapp Group - Technical changes reserved

Product Management www.lappkabel.de

You can find the current technical data in the corresponding data sheet.

PN 0456 / 02_03.16