



ÖLFLEX® LIFT

Flexible at cold temperatures, PVC lift cables with supporting element

Info

- High operating efficiency
- Suspension length up to 90 m
- VDE-tested and registered



Benefits

- Special cable design for a long service life
- Attractive price and maximum operational efficiency
- Very flexible due to extra-fine wire conductor design

Application range

- Lift cable that ensures the electrical integrity in various areas of lift construction
- Suitable for use in outdoor lifts
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3
- The assembly and handling guidelines for ÖLFLEX® CRANE cables can be found in the catalogue appendix, technical table T4; for ÖLFLEX® LIFT cables please see the catalogue appendix, technical table T5

Product features

- Flame-retardant according IEC 60332-1-2
- Good weather-resistance

Norm references / Approvals

- VDE registration under VDE reg. no. 7039

Product Make-up

- Strands of bare copper wires
- Special PVC-based core insulation
- Supporting element made of hemp or aramid
- Fleece-wrapping between cores and sheath
- Special PVC-based outer sheath

Technical data

	Classification ETIM 5.0 Class-ID: EC000826 ETIM 5.0 Class-Description: Elevator cable
	Core identification code Black with white numbers acc. to VDE 0293-1
	Suspension length refer to article table
	Conductor stranding Extra-fine wire according to VDE 0295, class 6/IEC 60228 class 6
	Minimum bending radius Flexible use: 20 x outer diameter
	Nominal voltage U ₀ /U: 300/500 V
	Test voltage 4000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Flexible use: -15°C to +70°C

Article number	Number of cores and mm ² per conductor	Outer diameter (mm)	Max. suspension length (m)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® LIFT					
0027020	7 G 1.0	11.5	80	67.2	178
0027022	12 G 1.0	16.3	80	115.2	332
0027024	18 G 1.0	16.4	70	172.8	405
0027027	24 G 1.0	19.4	60	230.4	533
0027029	36 G 1.0	25.1	90	345.6	887

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® LIFT T refer to page 168
- ÖLFLEX® LIFT S refer to page 169

Accessories

- Round cable wedged clamps
- KT cable shears refer to page 999