



ÖLFLEX® SOLAR XLR WP

Electron beam cross-linked solar cables with optimized performance in water - TÜV type



Info

- Optimised cable design - constant high volume resistance even after long-term period in water
- TÜV Type PV1-F (2 PFG 1169/08.2007)



Benefits

- The alternative for long-term storage in water, e.g. as it can occur in case after flooding or in buried conduits
- Reduction of flame propagation and of toxic combustion gases in the event of fire
- Robust against mechanical impacts
- Extruded colour stripe serves as reverse polarity protection during installation.
- Exact quantity control during installation by meter marking on the cable sheath

Application range

- For underground installation in conduits, in which water, heat and moisture can accumulate
- For the cabling between the solar modules and as extension cable between the module strings and the DC/AC inverter
- Gable and flat roof photovoltaic systems
- Photovoltaic plants and solar parks
- Suitable for direct burial: see data sheet

Product features

- Weather/UV-resistant acc. to HD 605/A1
- Ozone-resistant according to EN 50396
- Halogen-free and flame-retardant
- Good notch and abrasion resistance
- XLR WP = X-Linked Radiated Water-Proof Proven electron beam cross-linked quality

Norm references / Approvals

- PV1-F (TÜV type approved according to 2 PFG 1169/08.2007)

Product Make-up

- Fine-wire, tinned-copper conductor
- Core insulation made of electron beam cross-linked copolymer
- Colour of core insulation: white
- Outer sheath made of electron beam cross-linked copolymer
- Outer sheath colour: black respectively black with red or blue stripe

Technical data

	Classification ETIM 5.0 Class-ID: EC001578 ETIM 5.0 Class-Description: Flexible cable
	Conductor stranding Fine wire according to VDE 0295, class 5/IEC 60228 class 5
	Minimum bending radius Fixed installation: 4 x outer diameter
	Nominal voltage AC U_0/U : 600/1000 V DC U_0/U : 900/1500 V Max. permissible operating voltage: DC 1,8 kV (Conductor-conductor, non earthed system)
	Test voltage AC 6500 V
	Current rating In compliance with TÜV 2 PFG 1169/08.2007 table 1
	Temperature range -40°C to +120°C max. conductor temperature based on EN 60216-1 Ambient temperature according to TÜV 2 PFG 1169/08.07: -40°C to +90°C

Article number	Conductor cross-section (mm ²)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® SOLAR XLR WP				
Core insulation: white / Outer sheath: black				
1023501	2.5	5.2	24	48
1023502	4.0	5.6	38.4	65
1023503	6.0	6.2	57.6	88
1023504	10.0	7.4	96	135
1023505	16.0	8.7	153.6	207
Core insulation: white / Outer sheath: black with red stripe				
1023521	2.5	5.2	24	48
1023522	4.0	5.6	38.4	65
1023523	6.0	6.2	57.6	88
1023524	10.0	7.4	96	135
1023525	16.0	8.7	153.6	207
Core insulation: white / Outer sheath: black with blue stripe				
1023526	2.5	5.2	24	48
1023527	4.0	5.6	38.4	65
1023528	6.0	6.2	57.6	88
1023529	10.0	7.4	96	135
1023530	16.0	8.7	153.6	207

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request. Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges. Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
Packaging size: Coil 100 m; Drum (500; 1000) m
Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- EPIC® SOLAR 4 M refer to page 703
- EPIC® SOLAR 4 F refer to page 703
- UNIVERSAL STRIP stripping tool refer to page 1006
- KS 20 cable shears refer to page 999