



UNITRONIC® BUS PB FRNC FC
Fixed installation



i Info

- FRNC = Flame Retardant Non Corrosive
- Reduction of flame-propagation and density and toxicity of smoke gases in the event of fire
- Minimisation of damage to buildings and production facilities
- Safety for staff and in areas with high density of people

Benefits

- Halogen-free and highly flame-retardant
- Cables can be used for PROFIBUS-DP as well as PROFIBUS-FMS and FIP
- For use where the combination of a halogen-free outer sheath with properties similar to PUR and enhanced flame-retardance is required
- Fast Connect (FC) cable design

Application range

- This cable provides special advantages for use in sensitive areas where fire propagation must be avoided and the presence of toxic fumes would cause personal injury and damage to equipment.

Product features

- The cable is UL/CSA-certified (CMG)
- Halogen-free
- High flame retardancy in accordance with IEC 60332-3 and FT4
- Oil-resistant
- Based on the bit rates listed, in accordance with PNO specifications the following maximum cable lengths for a bus segment apply (cable type A, PROFIBUS-DP):
 93.75 kbit/s = 1200 m
 187.5 kbit/s = 400 m
 500 kbit/s = 200 m
 1.5 Mbit/s = 100 m

Product Make-up

- Solid, bare, single-wire copper conductor
- PE core insulation
- Inner sheath, screening foil and braiding
- Thermoplastic outer sheath
- Colour: violet (RAL 4001)

Technical data

- ETIM** 5.0 Class-ID: EC000830
ETIM 5.0 Class-Description: Data cable
- Certifications**
UL/CSA (CMG)
- Mutual capacitance**
Approx. 28.5 nF/km
- Peak operating voltage**
(not for power applications) 250 V
- Minimum bending radius**
80mm
- Test voltage**
Core/core: 1500 V rms
Core/screen: 1500 V
- Characteristic impedance**
(3 - 20 MHz): 150 ± 15 Ohm
- Temperature range**
-30°C to +80°C

Article number	Article designation	Number of pairs and conductor diameter (mm)	Outer diameter (mm)	Copper index (kg/km)	Weight (kg/km)
Fixed installation					
2170853	UNITRONIC® BUS PB FRNC FC	1 x 2 x 0.64	8	30.1	75

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.
 Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.
 Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths
 Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum
 Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).
 Lapp Kabel is a member of the PROFIBUS user organisation (PNO)
 Photographs are not to scale and do not represent detailed images of the respective products.

Accessories

- Sub-D Bus-Connectors
- FC STRIP stripping tool refer to page 1002

ÖLFLEX®
UNITRONIC®
ETHERLINE®
HITRONIC®
EPIC®
SKINTOP®
SILVYN®
FLEXIMARK®
ACCESSORIES
APPENDIX