

HSK-standard cable glands

HSK-K

Metr.



Material Polyamide V0 according to UL 94



Seal Buna-N



Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring




Operating Temperature -40 °C – 100 °C (-40 °F – 212 °F)

Colors grey (RAL 7035), black (RAL 9005),
blue (RAL 5012) for the intrinsic safety "i"



Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material e.g. Silicone upon request
- Other colors on request



AG	\varnothing mm	GL mm	H mm	\varnothing mm	Number grey	Number black	Number blue
M 12 x 1,5	3-6,5	8	21	15	1.209.1200.50	1.209.1201.50	1.209.1202.50
M 12 x 1,5	2-5	8	21	15	1.209.1200.51	1.209.1201.51	1.209.1202.51
M 16 x 1,5	4-8	8	22	19	1.209.1600.50	1.209.1601.50	1.209.1602.50
M 16 x 1,5	2-6	8	22	19	1.209.1600.51	1.209.1601.51	1.209.1602.51
M 16 x 1,5	5-10	8	25	22	1.219.1600.50	1.219.1601.50	1.219.1602.50
M 20 x 1,5	6-12	9	27	24	1.209.2000.50	1.209.2001.50	1.209.2002.50
M 20 x 1,5	5-9	9	27	24	1.209.2000.51	1.209.2001.51	1.209.2002.51
M 20 x 1,5	10-14	9	28	27	1.219.2000.50	1.219.2001.50	1.219.2002.50
M 25 x 1,5	13-18	11	31	30	1.219.2500.50	1.219.2501.50	1.219.2502.50
M 25 x 1,5	13-18	11	31	33	1.209.2500.50	1.209.2501.50	1.209.2502.50
M 25 x 1,5	9-16	11	31	33	1.209.2500.51	1.209.2501.51	1.209.2502.51
M 32 x 1,5	15-21	11	39	36	1.219.3200.50	1.219.3201.50	1.219.3202.50
M 32 x 1,5	18-25	11	39	42	1.209.3200.50	1.209.3201.50	1.209.3202.50
M 32 x 1,5	13-20	11	39	42	1.209.3200.51	1.209.3201.51	1.209.3202.51
M 40 x 1,5	19-27	13	47	46	1.219.4000.50	1.219.4001.50	1.219.4002.50
M 40 x 1,5	22-32	13	48	53	1.209.4000.50	1.209.4001.50	1.209.4002.50
M 40 x 1,5	20-26	13	48	53	1.209.4000.51	1.209.4001.51	1.209.4002.51
M 50 x 1,5	32-38	13	49	60	1.209.5000.50	1.209.5001.50	1.209.5002.50
M 50 x 1,5	25-31	13	49	60	1.209.5000.51	1.209.5001.51	1.209.5002.51
M 63 x 1,5	37-44	14	49	65/68	1.209.6300.50	1.209.6301.50	1.209.6302.50
M 63 x 1,5	29-35	14	49	65/68	1.209.6300.51	1.209.6301.51	1.209.6302.51

➔ Accessories see page 71

HSK-standard cable glands

Metr.-elongated

HSK-K



Material Polyamide V0 according to UL 94

Seal Buna-N


Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring

Operating Temperature -40 °C – 100 °C (-40 °F – 212 °F)

Colors grey (RAL 7035), black (RAL 9005), blue (RAL 5012) for the intrinsic safety "i"

Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material e.g. Silicone upon request
- Other colors on request



AG	∅k mm	GL mm	H mm	∅ mm	Number grey	Number black	Number blue
M 12 x 1,5	3-6,5	15	21	15	1.209.1200.30	1.209.1201.30	1.209.1202.30
M 12 x 1,5	2-5	15	21	15	1.209.1200.31	1.209.1201.31	1.209.1202.31
M 16 x 1,5	4-8	15	22	19	1.209.1600.30	1.209.1601.30	1.209.1602.30
M 16 x 1,5	2-6	15	22	19	1.209.1600.31	1.209.1601.31	1.209.1602.31
M 16 x 1,5	5-10	15	25	22	1.219.1600.30	1.219.1601.30	1.219.1602.30
M 20 x 1,5	6-12	15	27	24	1.209.2000.30	1.209.2001.30	1.209.2002.30
M 20 x 1,5	5-9	15	27	24	1.209.2000.31	1.209.2001.31	1.209.2002.31
M 20 x 1,5	10-14	15	28	27	1.219.2000.30	1.219.2001.30	1.219.2002.30
M 25 x 1,5	13-18	15	31	33	1.209.2500.30	1.209.2501.30	1.209.2502.30
M 25 x 1,5	9-16	15	31	33	1.209.2500.31	1.209.2501.31	1.209.2502.31
M 32 x 1,5	18-25	15	39	42	1.209.3200.30	1.209.3201.30	1.209.3202.30
M 32 x 1,5	13-20	15	39	42	1.209.3200.31	1.209.3201.31	1.209.3202.31
M 40 x 1,5	22-32	18	48	53	1.209.4000.30	1.209.4001.30	1.209.4002.30
M 40 x 1,5	20-26	18	48	53	1.209.4000.31	1.209.4001.31	1.209.4002.31
M 50 x 1,5	32-38	18	49	60	1.209.5000.30	1.209.5001.30	1.209.5002.30
M 50 x 1,5	25-31	18	49	60	1.209.5000.31	1.209.5001.31	1.209.5002.31
M 63 x 1,5	37-44	18	49	65/68	1.209.6300.30	1.209.6301.30	1.209.6302.30
M 63 x 1,5	29-35	18	49	65/68	1.209.6300.31	1.209.6301.31	1.209.6302.31

➔ Accessories see page 71

HSK-standard cable glands

HSK-K

PG



Material Polyamide V0 according to UL 94



Seal Buna-N



Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring


Operating Temperature -40 °C – 100 °C (-40 °F – 212 °F)

Colors grey (RAL 7035), black (RAL 9005),
blue (RAL 5012) for the intrinsic safety "i"



Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material e.g. Silicone upon request
- Other colors on request



AG	\varnothing mm	GL mm	H mm	\varnothing mm	Number grey	Number black	Number blue
PG 7	3-6,5	8	21	15	1.209.0700.14	1.209.0701.14	1.209.0702.14
PG 7	2-5	8	21	15	1.209.0700.15	1.209.0701.15	1.209.0702.15
PG 9	4-8	8	22	19	1.209.0900.14	1.209.0901.14	1.209.0902.14
PG 9	2-6	8	22	19	1.209.0900.15	1.209.0901.15	1.209.0902.15
PG 11	5-10	8	25	22	1.209.1100.14	1.209.1101.14	1.209.1102.14
PG 11	3-7	8	25	22	1.209.1100.15	1.209.1101.15	1.209.1102.15
PG 13,5	6-12	9	27	24	1.209.1300.14	1.209.1301.14	1.209.1302.14
PG 13,5	5-9	9	27	24	1.209.1300.15	1.209.1301.15	1.209.1302.15
PG 16	10-14	10	28	27	1.209.1600.14	1.209.1601.14	1.209.1602.14
PG 16	7-12	10	28	27	1.209.1600.15	1.209.1601.15	1.209.1602.15
PG 21	13-18	11	31	33	1.209.2100.14	1.209.2101.14	1.209.2102.14
PG 21	9-16	11	31	33	1.209.2100.15	1.209.2101.15	1.209.2102.15
PG 29	18-25	11	39	42	1.209.2900.14	1.209.2901.14	1.209.2902.14
PG 29	13-20	11	39	42	1.209.2900.15	1.209.2901.15	1.209.2902.15
PG 36	22-32	13	48	53	1.209.3600.14	1.209.3601.14	1.209.3602.14
PG 36	20-26	13	48	53	1.209.3600.15	1.209.3601.15	1.209.3602.15
PG 42	32-38	13	49	60	1.209.4200.14	1.209.4201.14	1.209.4202.14
PG 42	25-31	13	49	60	1.209.4200.15	1.209.4201.15	1.209.4202.15
PG 48	37-44	14	49	65	1.209.4800.14	1.209.4801.14	1.209.4802.14
PG 48	29-35	14	49	65	1.209.4800.15	1.209.4801.15	1.209.4802.15

Advice: see page 18 for further polyamide cable glands with special clamping ranges in PG threads

➔ Accessories see page 71

HSK-standard cable glands

HSK-K

PG-elongated

RoHS



Material Polyamide V0 according to UL 94

Seal Buna-N


Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring

Operating Temperature -40 °C – 100 °C (-40 °F – 212 °F)

Colors grey (RAL 7035), black (RAL 9005), blue (RAL 5012) for the intrinsic safety "i"



- Advice:**
- With additional pre-assembled O-Ring upon request
 - Please find suitable O-Ring on page 86
 - Other sealing material e.g. Silicone upon request
 - Other colors on request




AG	\varnothing mm	GL mm	H mm	\varnothing mm	Number grey	Number black	Number blue
PG 7	3 – 6,5	15	21	15	1.209.0700.60	1.209.0701.60	1.209.0702.60
PG 7	2 – 5	15	21	15	1.209.0700.61	1.209.0701.61	1.209.0702.61
PG 9	4 – 8	15	22	19	1.209.0900.60	1.209.0901.60	1.209.0902.60
PG 9	2 – 6	15	22	19	1.209.0900.61	1.209.0901.61	1.209.0902.61
PG 11	5 – 10	15	25	22	1.209.1100.60	1.209.1101.60	1.209.1102.60
PG 11	3 – 7	15	25	22	1.209.1100.61	1.209.1101.61	1.209.1102.61
PG 13,5	6 – 12	15	27	24	1.209.1300.60	1.209.1301.60	1.209.1302.60
PG 13,5	5 – 9	15	27	24	1.209.1300.61	1.209.1301.61	1.209.1302.61
PG 16	10 – 14	15	28	27	1.209.1600.60	1.209.1601.60	1.209.1602.60
PG 16	7 – 12	15	28	27	1.209.1600.61	1.209.1601.61	1.209.1602.61
PG 21	13 – 18	15	31	33	1.209.2100.60	1.209.2101.60	1.209.2102.60
PG 21	9 – 16	15	31	33	1.209.2100.61	1.209.2101.61	1.209.2102.61
PG 29	18 – 25	15	39	42	1.209.2900.60	1.209.2901.60	1.209.2902.60
PG 29	13 – 20	15	39	42	1.209.2900.61	1.209.2901.61	1.209.2902.61
PG 36	22 – 32	18	48	53	1.209.3600.60	1.209.3601.60	1.209.3602.60
PG 36	20 – 26	18	48	53	1.209.3600.61	1.209.3601.61	1.209.3602.61
PG 42	32 – 38	18	49	60	1.209.4200.60	1.209.4201.60	1.209.4202.60
PG 42	25 – 31	18	49	60	1.209.4200.61	1.209.4201.61	1.209.4202.61
PG 48	37 – 44	18	49	65	1.209.4800.60	1.209.4801.60	1.209.4802.60
PG 48	29 – 35	18	49	65	1.209.4800.61	1.209.4801.61	1.209.4802.61

➔ Accessories see page 71

HSK-standard cable glands



HSK-KE
PG



Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material and colors upon request


Material	Polyamide V0 according to UL 94
Seal	Buna-N
Protection	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) within the specified clamping range, only with optional O-Ring
Operating Temperature	-40 °C – 100 °C (-40 °F – 212 °F)
Colors	grey (RAL 7035), black (RAL 9005)

AG	\varnothing mm	d mm	GL mm	H mm	\varnothing mm	Number grey	Number black
PG 7	4 – 8	7	8	22	19	1.590.0700.14	1.590.0701.14
PG 7	2 – 6	7	8	22	19	1.590.0700.15	1.590.0701.15
PG 9	5 – 10	9	8	25	22	1.590.0900.14	1.590.0901.14
PG 9	3 – 7	9	8	25	22	1.590.0900.15	1.590.0901.15
PG 11	6 – 12	10,5	8	24	24	1.590.1100.14	1.590.1101.14
PG 11	5 – 9	10,5	8	24	24	1.590.1100.15	1.590.1101.15
PG 13,5	10 – 14	12,5	9	28	27	1.590.1300.14	1.590.1301.14
PG 13,5	7 – 12	12,5	9	28	27	1.590.1300.15	1.590.1301.15
PG 16	13 – 18	15	10	31	33	1.590.1600.14	1.590.1601.14
PG 16	9 – 16	15	10	31	33	1.590.1600.15	1.590.1601.15

➔ Accessories see page 71



HSK-KR
PG



Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material and colors upon request

Material	Polyamide V0 according to UL 94
Seal	Buna-N
Protection	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) within the specified clamping range, only with optional O-Ring
Operating Temperature	-40 °C – 100 °C (-40 °F – 212 °F)
Colors	grey (RAL 7035), black (RAL 9005)

AG	\varnothing mm	GL mm	H mm	\varnothing mm	Number grey	Number black
PG 9	3 – 6,5	8	21	19	1.591.0900.14	1.591.0901.14
PG 9	2 – 5	8	21	19	1.591.0900.15	1.591.0901.15
PG 11	4 – 8	8	22	22	1.591.1100.14	1.591.1101.14
PG 11	2 – 6	8	22	22	1.591.1100.15	1.591.1101.15
PG 13,5	5 – 10	9	25	24	1.591.1300.14	1.591.1301.14
PG 13,5	3 – 7	9	25	24	1.591.1300.15	1.591.1301.15
PG 16	6 – 12	10	27	27	1.591.1600.14	1.591.1601.14
PG 16	5 – 9	10	27	27	1.591.1600.15	1.591.1601.15
PG 21	10 – 14	11	28	33	1.591.2100.14	1.591.2101.14
PG 21	7 – 12	11	28	33	1.591.2100.15	1.591.2101.15

➔ Accessories see page 71

HSK-standard cable glands

HSK-K

NPT

RoHS



Material Polyamide V0 according to UL 94


Seal Buna-N

Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring

Operating Temperature -40 °C – 100 °C (-40 °F – 212 °F)

Colors grey (RAL 7035), black (RAL 9005), blue (RAL 5012) for the intrinsic safety "i"

- Advice:**
- With additional pre-assembled O-Ring upon request
 - Please find suitable O-Ring on page 86
 - Other sealing material e.g. Silicone upon request
 - Other colors on request




AG	∅k mm	GL mm	H mm	∅ mm	Number grey	Number black	Number blue
3/8" NPT	4 – 8	15	22	19/22	1.209.3800.70	1.209.3801.70	1.209.3802.70
3/8" NPT	2 – 6	15	22	19/22	1.209.3800.71	1.209.3801.71	1.209.3802.71
1/2" NPT	6 – 12	13	27	24	1.209.1200.70	1.209.1201.70	1.209.1202.70
1/2" NPT	5 – 9	13	27	24	1.209.1200.71	1.209.1201.71	1.209.1202.71
1/2" NPT/16	10 – 14	13	28	27	1.209.1216.70	1.209.1217.70	1.209.1218.70
1/2" NPT/16	7 – 12	13	28	27	1.209.1216.71	1.209.1217.71	1.209.1218.71
3/4" NPT	13 – 18	14	31	33	1.209.3400.70	1.209.3401.70	1.209.3402.70
3/4" NPT	9 – 16	14	31	33	1.209.3400.71	1.209.3401.71	1.209.3402.71
1" NPT	18 – 25	19	39	42	1.209.1000.70	1.209.1001.70	1.209.1002.70
1" NPT	13 – 20	19	39	42	1.209.1000.71	1.209.1001.71	1.209.1002.71
1 1/4" NPT	18 – 25	16	39	42/46	1.209.5400.70	1.209.5401.70	1.209.5402.70
1 1/4" NPT	13 – 20	16	39	42/46	1.209.5400.71	1.209.5401.71	1.209.5402.71
1 1/2" NPT	22 – 32	20	48	53	1.209.6400.70	1.209.6401.70	1.209.6402.70
1 1/2" NPT	20 – 26	20	48	53	1.209.6400.71	1.209.6401.71	1.209.6402.71

➔ Accessories see page 71

HSK-standard cable glands


HSK-K-PVDF
Metr.



Advice:


- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material and colors upon request

Material	PVDF V0 according to UL 94
Seal	FPM
Protection	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) within the specified clamping range, only with optional O-Ring
Operating Temperature	-35 °C – 150 °C (-31 °F – 302 °F)
Colors	nature



Accessories see page 71


HSK-K-PVDF
NPT



Advice:

- With additional pre-assembled O-Ring upon request
- Please find suitable O-Ring on page 86
- Other sealing material and colors upon request

Material	PVDF V0 according to UL 94
Seal	FPM
Protection	IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG) within the specified clamping range, only with optional O-Ring
Operating Temperature	-35 °C – 150 °C (-31 °F – 302 °F)
Colors	nature



Accessories see page 71

HSK-standard cable glands

HSK-K-PVDF

PG

RoHS



Material PVDF V0 according to UL 94


Seal FPM

Protection IP 68 – 10 bar / IP 69K (NEMA 6 – 150 PSIG)
within the specified clamping range, only with optional O-Ring

Operating Temperature -35 °C – 150 °C (-31 °F – 302 °F)

Colors nature

- Advice:**
- With additional pre-assembled O-Ring upon request
 - Please find suitable O-Ring on page 86
 - Other sealing material e.g. Silicone upon request
 - Other colors on request



AG	∅ mm	GL mm	H mm	∅ mm	Number
PG 7	3 – 6,5	8	21	15	1.299.0700.14
PG 7	2 – 5	8	21	15	1.299.0700.15
PG 9	4 – 8	8	22	19	1.299.0900.14
PG 9	2 – 6	8	22	19	1.299.0900.15
PG 11	5 – 10	8	25	22	1.299.1100.14
PG 11	3 – 7	8	25	22	1.299.1100.15
PG 13,5	6 – 12	9	27	24	1.299.1300.14
PG 13,5	5 – 9	9	27	24	1.299.1300.15
PG 16	10 – 14	10	28	27	1.299.1600.14
PG 16	7 – 12	10	28	27	1.299.1600.15
PG 21	13 – 18	11	31	33	1.299.2100.14
PG 21	9 – 16	11	31	33	1.299.2100.15
PG 29	18 – 25	11	39	42	1.299.2900.14
PG 29	13 – 20	11	39	42	1.299.2900.15
PG 36	22 – 32	13	48	53	1.299.3600.14
PG 36	20 – 26	13	48	53	1.299.3600.15
PG 42	32 – 38	13	49	60	1.299.4200.14
PG 42	25 – 31	13	49	60	1.299.4200.15
PG 48	37 – 44	14	49	65	1.299.4800.14
PG 48	29 – 35	14	49	65	1.299.4800.15

➔ Accessories see page 71