



SKINTOP® INOX / SKINTOP® INOX-R

Info

- Stainless steel version with compact design
- For use in the **splash zone** in the food production



Benefits

- Corrosion-resistant
- Sea water-resistant
- Smooth surfaces - no edges
- Compact design
- Wide, variable clamping ranges

Application range

- Onshore and offshore applications
- Bottling plants and breweries
- Food industry (product-free zone, splash zone)

Norm references / Approvals

- **ECOLAB®**
Industry standard in the field of professional cleaning and disinfection
- **DIN EN 1672-2**
Guideline for the design of machinery
- **DIN EN ISO 14 159**
Security of machinery Hygienic requirements for the design of machinery

Product Make-up

- Metric connection thread acc. to DIN EN 60423
- Basis for technical information EN 50262

Note

- Size M 40x1,5 available on request

Technical data

Classification
ETIM 5.0 Class-ID: EC000441
ETIM 5.0 Class-Description: Cable screw gland

Material
Body: Stainless steel - V4A (1.4404 / 316L)
Insert: Polyamide
Sealing ring: Silicone
O-Ring: Silicone

Protection rating
IP 68 - 10 bar (M12 - M20)
IP 68 - 5 bar (M25 - M32)
IP 69

Temperature range
-40°C to +100°C

Article number	Article designation / size	Clamping range ØF (mm)	Thread length, D (mm)	SW wrench size mm	Overall length, C (mm)	Pieces / PU
SKINTOP® INOX						
53806739	12x1,5	4-7	6.5	16	29.3	5
53806740	16x1,5	6-10	7	20	32.4	5
53806741	20x1,5	7-13	8	24	35.8	5
53806742	25x1,5	9-17	8	29	37.8	5
53806743	32x1,5	11-21	9	36	43.3	5
SKINTOP® INOX-R						
53806749	12x1,5	3-5	6.5	16	29.3	5
53806750	16x1,5	5-7	7	20	32.4	5
53806751	20x1,5	5-10	8	24	35.8	5
53806752	25x1,5	7-13	8	29	37.8	5
53806753	32x1,5	7-15	9	36	43.3	5

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- SKINDICHT® CN-M refer to page 759
- SKINTOP® HYGIENIC

Accessories

- Suitable counter nut SKINDICHT® SM CrNi M

