

iglidur® round bars | Product range

Used to prevent electro-static charges – iglidur® F2



Order key for round bars

Type	Dimensions [mm]
SF R F2-30 00-□	
Bar stock	Round bar
iglidur® material	
Outer Ø	Inner Ø
Length	

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

Ø	Lengths	Part No.
10	50–1,000	SFRF2-1000-□
15	50–1,000	SFRF2-1500-□
20	50–1,000	SFRF2-2000-□
25	50–1,000	SFRF2-2500-□
30	50–1,000	SFRF2-3000-□
35	50–1,000	SFRF2-3500-□
40	50–1,000	SFRF2-4000-□
45	50–1,000	SFRF2-4500-□

Versatile and cost-effective – iglidur® J2



Order key for round bars

Type	Dimensions [mm]
SF R J2-30 00-□	
Bar stock	Round bar
iglidur® material	
Outer Ø	Inner Ø
Length	

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

Ø	Lengths	Part No.
10	50–1,000	SFRJ2-1000-□
15	50–1,000	SFRJ2-1500-□
20	50–1,000	SFRJ2-2000-□
25	50–1,000	SFRJ2-2500-□
30	50–1,000	SFRJ2-3000-□
35	50–1,000	SFRJ2-3500-□
40	50–1,000	SFRJ2-4000-□
45	50–1,000	SFRJ2-4500-□

Available from stock
Upon request/check availability

iglidur® round bars | Product range

For the rail industry, flame-retardant, complies with DIN EN 45545 HL3, R22/R23 – iglidur® RW370



Order key for round bars

Type	Dimensions [mm]
SF R RW370-30 00-□	
Bar stock	Round bar
iglidur® material	
Outer Ø	Inner Ø
Length	

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

Ø	Lengths	Part No.
10	50–1,000	SFRRW370-1000-□
15	50–1,000	SFRRW370-1500-□
20	50–1,000	SFRRW370-2000-□
25	50–1,000	SFRRW370-2500-□
30	50–1,000	SFRRW370-3000-□
35	50–1,000	SFRRW370-3500-□
40	50–1,000	SFRRW370-4000-□
45	50–1,000	SFRRW370-4500-□

For long service life under extreme loads – iglidur® Q2



Order key for round bars

Type	Dimensions [mm]
SF R Q2-30 00-□	
Bar stock	Round bar
iglidur® material	
Outer Ø	Inner Ø
Length	

In your required length, freely selectable between 50 and 1,000mm. Cut-to-size parts are delivered oversized.

Dimensions [mm]

Ø	Lengths	Part No.
10	50–1,000	SFRQ2-1000-□
15	50–1,000	SFRQ2-1500-□
20	50–1,000	SFRQ2-2000-□
25	50–1,000	SFRQ2-2500-□
30	50–1,000	SFRQ2-3000-□
35	50–1,000	SFRQ2-3500-□
40	50–1,000	SFRQ2-4000-□
45	50–1,000	SFRQ2-4500-□

Ø	Lengths	Part No.
50	50–1,000	SFRQ2-5000-□
55	50–1,000	SFRQ2-5500-□
60	50–1,000	SFRQ2-6000-□
65	50–1,000	SFRQ2-6500-□
70	50–1,000	SFRQ2-7000-□
80	50–1,000	SFRQ2-8000-□
90	50–1,000	SFRQ2-9000-□
100	50–1,000	SFRQ2-10000-□

igus® constantly expands its range of available materials and dimensions. Please contact us in case the required diameter is not available.