

KLIKSEAL

Product Features TKS KLIKSEAL®

Height of only 17- 20mm, 5.5 - 5.7mm on the outside depending on size. Cable glands are approx. 30 - 40mm

Handles a large range of cable and pipe diameters

Installation time saving of up to 90%

Self-adjusting to wall thickness

Ergonomic Installation

"Pushout" membrane

Fixed in both directions when mounted

Space saving design



Integrated tension relief

KLIK = No material compression during installation

IP65

Rubber coated tension relief for protection of the cable mantle



Centre the KLIKSEAL in the opening (from the inside), push evenly with both thumbs until it "klicks" into place



Insert the cable from the side with the polyamide tabs



Note! KLIKSEAL® is installed from the inside.

KLIKSEAL®



Material: TPE and Polyamide 66 - Halogen Free UL approved material
 Integrated cable anchorage, wide sealing range.
 Material thickness 1.5 - 5mm
 Material thickness IP67/65 2-5mm
 Quick and simple assembly without the use of tools.

Mode of protection: IP65
 Temperature range: -20° to +125°C⁽¹⁾
 Test standard: EN60529:1991 + A1
 EN50262: 1998
 EMKO-TUI (03-SEC) FI001/84
 606620

Semko report: 606620

*Cable Anchorage Type A, according to EN50262
 ** 8.1 - 8.9mm only approved for tension relief
 (1) Unstressed material

Part No	Size	IP65 and Cable Anchorage Type A* for Cable Ø mm	IP65 for Cable Ø mm	A mm	B for IP67/65 mm	H mm	H2 mm	D1 mm	D*** mm	Pcs pack
---------	------	---	---------------------	------	------------------	------	-------	-------	---------	----------

Light Grey - RAL 7035

TST1475803	M20	7-11	4-11	20.5	2-5	17-20	5.5	4.0	29.3-34.5	50
TST1475804	M25	7-13**	4-13	25.5	2-5	17-20	5.7	5.0	34.3-40.0	50

Black - RAL 9005

TST1475813	M20	7-11	4-11	20.5	2-5	17-20	5.5	4.0	29.3-34.5	50
TST1475814	M25	7-13**	4-13	25.5	2-5	17-20	5.7	5.0	34.3-40.0	50

White - RAL 9010

TST1475823	M20	7-11	4-11	20.5	2-5	17-20	5.5	4.0	29.3-34.5	50
TST1475824	M25	7-13**	4-13	25.5	2-5	17-20	5.7	5.0	34.3-40.0	50

*** = varies depending on thickness of material installed in.

KLIKSEAL® for thin materials



Material: TPE and Polyamide 66 - Halogen Free UL approved material
 Integrated cable anchorage, wide sealing range.
 Material thickness 0.5 - 3mm
 Material thickness IP67/65 0.5-3mm
 Quick and simple assembly without the use of tools.

Mode of protection: IP65
 Temperature range: -20° to + 125°C⁽¹⁾
 Test standard: EN60529:1991 + A1
 EN50262: 1998
 EMKO-TUI (03-SEC) FI001/84
 N/A

Semko report: N/A

*Cable Anchorage Type A, according to EN50262
 ** 8.1 - 8.9mm only approved for tension relief
 (1) Unstressed material

Part No	Size	IP65 and Cable Anchorage Type A* for Cable Ø mm	IP65 for Cable Ø mm	A mm	B for IP67/65 mm	H mm	H2 mm	D1 mm	D*** mm	Pcs pack
---------	------	---	---------------------	------	------------------	------	-------	-------	---------	----------

Light Grey - RAL 7035

TST1475807	M20	7-11	4-11	20.5	0.5-3mm	17-20	5.5	4.0	34.2-37.2	50
TST1475808	M25	7-13**	4-13	25.5	0.9-3mm	17-20	5.7	5.0	39.2-42.2	50

Black - RAL 9005

TST1475817	M20	7-11	4-11	20.5	0.5-3mm	17-20	5.5	4.0	34.2-37.2	50
TST1475818	M25	7-13**	4-13	25.5	0.9-3mm	17-20	5.7	5.0	39.2-42.2	50

White - RAL 9010

TST1475827	M20	7-11	4-11	20.5	0.5-3mm	17-20	5.5	4.0	34.2-37.2	50
TST1475828	M25	7-13**	4-13	25.5	0.9-3mm	17-20	5.7	5.0	39.2-42.2	50

*** = varies depending on thickness of material installed in.