

1

Shielded Multi-Conductor FT-4

Stranded Tinned Copper Conductors



Part Number	Conductor			Drain AWG Size	Wall Thickness		Outer Diameter	Total Weight	Colour Code
	No	AWG Size	Stranding		Insulation	Jacket			
5032402TFT4	2	24	7 x 32	24	.015	.020	.150	46	ECl Chart 1
5032202TFT4	2	22	7 x 30	24	.015	.020	.162	57	1
5032203TFT4	3	22	7 x 30	24	.015	.023	.184	73	1
5032204TFT4	4	22	7 x 30	24	.015	.023	.200	93	1
5032205TFT4	5	22	7 x 30	24	.015	.023	.202	99	1
5032002TFT4	2	20	7 x 28	22	.015	.023	.187	73	1
5032003TFT4	3	20	7 x 28	22	.015	.023	.197	93	1
5032004TFT4	4	20	7 x 28	22	.015	.023	.216	133	1
5031802TFT4	2	18	16 x 30	20	.015	.023	.210	100	1
5031803TFT4	3	18	16 x 30	20	.015	.023	.222	127	1
5031804TFT4	4	18	16 x 30	20	.015	.023	.242	153	1
5031602TFT4	2	16	26 x 30	18	.015	.023	.236	133	1
5031603TFT4	3	16	26 x 30	18	.015	.023	.242	168	1
5031604TFT4	4	16	26 x 30	18	.015	.023	.265	207	1
5031402TFT4	2	14	41 x 30	16	.030	.030	.338	233	1
5031403TFT4	3	14	41 x 30	16	.030	.030	.359	300	1
5031404TFT4	4	14	41 x 30	16	.030	.030	.394	373	1
5031202TFT4	2	12	65 x 30	14	.030	.030	.376	312	1
5031203TFT4	3	12	65 x 30	14	.030	.030	.400	412	1
5031204TFT4	4	12	65 x 30	14	.030	.030	.440	520	1

All measurements in imperial i.e inches, lbs.

Individually Foil Shielded Multi-Pair FT-4

Stranded Tinned Copper Conductors



Part Number	Pair			Wall Thickness		Outer Diameter	Nom. Cap.		Total Weight
	No	AWG Size	Stranding	Insulation	Jacket		pF/ft A**	pF/ft B***	
5822252TFT4	2	22	7 x 30	.010	.018	.165	35	62	65

All measurements in imperial i.e inches, lbs.