

1

Multi-Pair Foil & Braid Shield FT-4

Stranded Tinned Copper Conductors



Part Number	Pair			Wall Thickness		Outer Diameter	Total Weight	Colour Code
	No	AWG Size	Stranding	Insulation	Jacket			
5302452TFT4	2	24	7 x 32	.030	.226	82	13.7	ECI Chart 5
5302453TFT4	3	24	7 x 32	.030	.239	99	13.7	5
5302454TFT4	4	24	7 x 32	.030	.262	118	13.7	5
5302455TFT4	5	24	7 x 32	.030	.289	137	13.7	5
5302456TFT4	6	24	7 x 32	.030	.297	153	13.7	5
5302457STFT4	7.5	24	7 x 32	.030	.303	175	13.7	5
5302458TFT4	8	24	7 x 32	.030	.342	192	13.7	5
5302459TFT4	9	24	7 x 32	.030	.347	202	13.7	5
5302460TFT4	10	24	7 x 32	.030	.369	230	13.7	5
5302461TFT4	11	24	7 x 32	.030	.375	238	13.7	5
5302462TFT4	12	24	7 x 32	.030	.382	258	13.7	5
5302463STFT4	13.7	24	7 x 32	.030	.382	263	13.7	5
5302469TFT4	19	24	7 x 32	.030	.460	367	13.7	5
5302475TFT4	25	24	7 x 32	.045	.530	524	13.7	5

All measurements in imperial i.e inches, lbs.

Individually Foil Shielded Multi-Pair FT-4

Low Capacitance



Part Number	Pair			Wall Thickness		Outer Diameter	Total Weight	Colour Code
	No	AWG Size	Stranding	Insulation	Jacket			
5862452TFT4	2	24	7 x 32	.030	.228	89	18.5	ECI Chart 3
5862453TFT4	3	24	7 x 32	.030	.243	112	18.5	3
5862454TFT4	4	24	7 x 32	.030	.268	139	18.5	3
5862456TFT4	6	24	7 x 32	.030	.307	188	18.5	3
5862459TFT4	9	24	7 x 32	.030	.363	263	18.5	3
5862462TFT4	12	24	7 x 32	.030	.404	336	18.5	3
5862465TFT4	15	24	7 x 32	.030	.443	406	18.5	3
5862477TFT4	27	24	7 x 32	.049	.652	765	18.5	3

All measurements in imperial i.e inches, lbs.