

---

 TECHNICAL DATA SHEET

# PMAJACK - C.66 - Braided Hose

## PMA



Fire safety bundling and protection of cables and wire in applications where high standards are required

CE

**Applications:**

- Industry, construction of vehicles and trains

**Features & Benefits:**

- Coverage: > 75%
- Excellent abrasion properties
- Lightweight structure
- High flexibility
- Self-extinguishing

**Materials:**

- Polyamide 6.6

**Compatible with:**

- PMAJACK terminations

**Temperature range:**

- -55°C ... +135°C continuous, +160°C short-term

**Conforms to:**

- EN 45545-2 HL3 (R22 & R23)
- NFPA 130
- UL94 V2

**Construction:**

- According to DIN 65164 (part 1 and 2)
- Stand Ø: 0.28 mm

**Colour:**

- Black
- Grey

**Chemical properties:**

- Please refer to [www.pma.ch](http://www.pma.ch)  
(Technical Information / Chemical Resistance)


**Environmental properties:**

- Free from halogens and cadmium
- RoHS and REACH compliant

**Product selection:**

Part no.		Construction	Braid size	fits to	Range of application		Weight	Packing unit
black	grey	numb. x Ø mm	NW	PMA terminations	min. Ø mm	max. Ø mm	kg/100 m	metre
C.66.10SW	C.66.10GR	80 x 0.28	10	SRER-06	8.0	14.0	0.7	50
C.66.12SW	C.66.12GR	120 x 0.28	12	SRER-06	9.0	18.0	0.9	50
C.66.16SW	C.66.16GR	144 x 0.28	16	SRER-06 / SRER-16	11.0	22.0	1.2	50
C.66.20SW	C.66.20GR	192 x 0.28	20	SRER-16 / SRER-21	14.0	26.0	1.6	50
C.66.25SW	C.66.25GR	168 x 0.28	25	SRER-16 / SRER-21	18.0	26.0	1.3	50
C.66.30SW	C.66.30GR	288 x 0.28	30	SRER-21 / SRER-29	25.0	43.0	3.2	50
C.66.40SW	C.66.40GR	288 x 0.28	40	SRER-29	30.0	52.0	2.5	50
C.66.45SW	-	480 x 0.28	45	SREV-40 / SRER-50	40.0	73.0	4.0	60

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-55 ... +135°C		PMA DO 9.21-4510
Short-term	+160°C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Flammability class	V2		UL 94
Fire hazard level	HL3		EN 45545-2 (R22)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 150 Ds max.		EN ISO 5659-2 (25 kW/m <sup>2</sup> )
Toxicity	< 0.75 CIT <sub>NLP</sub>		NF X 70-100-1/-2: (600°C)
Fire hazard level	HL3		EN 45545-2 (R23)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 300 Ds max.		EN ISO 5659-2 (25 kW/m <sup>2</sup> )
Toxicity	< 1.5 CIT <sub>NLP</sub>		NF X 70-100-1/-2: (600°C)

Fire performance:		
- Flammability	compliant	ASTM E 162
- Smoke density	compliant	ASTM E 662

ABB Switzerland Ltd,  
PMA Cable Protection  
Aathalstrasse 90  
8610 Uster, Switzerland  
Phone: +41 58 585 00 11  
pma-info@ch.abb.com  
www.pma.ch

Let's write the future.  
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

