

 TECHNICAL DATA SHEET

PMAJACK - B.PX - Braided Hose

PMA



Fire safety bundling and protection of cables and wire in applications where the combination of lightweight structure, low volume and flexibility is required.

CE

Applications:

- Industry, construction of vehicles and trains

Features & Benefits:

- Coverage: > 50%
- Excellent abrasion properties
- Lightweight structure
- High flexibility
- Excellent flame-retardant properties

Materials:

- Polyester

Temperature range:

- -50°C ... +120°C continuous, +150°C short-term

Conforms to:

- EN 45545-2 HL3 (R22 & R23)
- UL94 V0

Construction:

- Strand Ø: 0.20 mm

Colour:

- Black

Chemical properties:

- Please refer to www.pma.ch
(Technical Information / Chemical Resistance)


Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:

Part no.	Construction numb. x Ø mm	Braid size NW	Range of application		Weight kg/100 m	Packing unit metre
			min. Ø mm	max. Ø mm		
B.PX.12SW	96 x 0.20	12	6.0	18.0	0.5	100
B.PX.15SW	144 x 0.20	15	10.0	28.0	0.7	100
B.PX.30SW	192 x 0.20	30	20.0	42.0	0.9	100

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Thermal properties:	Value:	Test parameters:	Test method:
Continuous application temperature	-50 ... +120°C		PMA DO 9.21-4510
Short-term	+150°C	(168 h)	PMA DO 9.21-4360

Fire safety properties:	Value:	Test parameters:	Test method:
Flammability class	V0		UL 94
Fire hazard level	HL3		EN 45545-2 (R22)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 150 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 0.75 CIT _{NLP}		NF X 70-100-1/-2: (600°C)
Fire hazard level	HL3		EN 45545-2 (R23)
Oxygen index	> 32 %		EN ISO 4589-2
Smoke density	< 300 Ds max.		EN ISO 5659-2 (25 kW/m ²)
Toxicity	< 1.5 CIT _{NLP}		NF X 70-100-1/-2: (600°C)

ABB Switzerland Ltd,
PMA Cable Protection
Aathalstrasse 90
8610 Uster, Switzerland
Phone: +41 58 585 00 11
pma-info@ch.abb.com
www.pma.ch

Let's write the future.
Together. **abb.com**

We reserve the right to make technical changes or modify the contents of this document without prior notice. With regard to purchase orders, the agreed particulars shall prevail. ABB Installation Products Inc. does not accept any responsibility whatsoever for potential errors or possible lack of information in this document.

We reserve all rights in this document and in the subject matter and illustrations contained therein. Any reproduction, disclosure to third parties or utilization of its contents – in whole or in parts – is forbidden without prior written consent of ABB Inc. Copyright© 2019 ABB Installation Products Inc. All rights reserved

