

# Safety Contactors

## POSITIVELY-GUIDED CONTACTORS



**Features**

- Positively guided contacts.
- Mechanically linked main and auxiliary contacts.
- Auxiliary contacts are PLC compatible.
- Auxiliary contacts cannot be removed. (< 85 Amps)
- Contactors are suitable for up to Safety Category 4 (AS 4024-2006).

### Contactors with AC coil up to 85 Amps

CAS 7-9-14C240VAC - 9 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-12-14C240VAC - 12 Amps, 1NO,4NC contacts 240 VAC Coil
CAS 7-16-14C240VAC - 16 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-23-14C240VAC - 23 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-30-14C240VAC - 30 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-37-14C240VAC - 37 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-43-14C240VAC - 43 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-60-14C240VAC - 60 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-72-14C240VAC - 72 Amps, 1NO, 4NC contacts 240 VAC coil
CAS 7-85-14C240VAC - 85 Amps, 1NO, 4NC contacts 240 VAC coil

\*CRC-7-280 Surge Suppressor (110-280VAC)

CR7-IE Interface Module 24VDC/240VAC

### Contactors with DC Coil up to 85 Amps

CAS 7-9E-14C24VDC - 9 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-12E-14C24VDC - 12 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-16E-14C24VDC - 16 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-23E-14C24VDC - 23 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-30E-14C24VDC - 30 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-37E-14C24VDC - 37 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-43E-14C24VDC - 43 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-60D-14C24VDC - 60 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-72D-14C24VDC - 72 Amps, 1NO, 4NC contacts 24 VDC coil
CAS 7-85D-14C24VDC - 85 Amps, 1NO, 4NC contacts 24 VDC coil

### Contactors higher than 85 Amps

CAS6 110EI-22-240VAC - 110 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 140EI-22-240VAC - 140 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 180EI-22-240VAC - 180 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 210EI-22-240VAC - 210 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 250EI-22-240VAC - 250 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 300EI-22-240VAC - 300 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 420EI-22-240VAC - 420 Amps, 2NO 2NC contact with 24 VDC/240 VAC module
CAS6 630EI-22-240VAC - 630 Amps, 2NO 2NC contact with 24VDC/240VAC module
CAS6 860EI-22-240VAC - 860 Amps, 2NO 2NC contact with 24VDC/240VAC module