

Thermo plastic enclosures

Size 32.13

CQ 08 I	CQ 08 IA	CQ 08 IAP
<p>Technical drawings for CQ 08 I showing dimensions: 18.5, 46, 19.5, 28.7, 34.</p>	<p>Technical drawings for CQ 08 IA showing dimensions: 46, 17.8, 37.25, 39.5, 54.5, 30, 38, 46, 34.5.</p>	<p>Technical drawings for CQ 08 IAP showing dimensions: 46, 17.8, 37.25, 39.5, 54.5, 30, 15, 38, 46, 20.25, 34.5.</p>

CQ 08 V	CQ 08 VA	MQ 08 VO225
<p>Technical drawings for CQ 08 V showing dimensions: PG 21, 48, 15, 54, 28.7, 35.</p>	<p>Technical drawings for CQ 08 VA showing dimensions: PG 16, 48, 54, 28.7, 35.</p>	<p>Technical drawings for MQ 08 VO225 showing dimensions: 30, M25x1.5, 30, 48, 70, 28.5, 35.</p>

CQ 08 VG	CQ 08 C & CQ 08 CA	CRQ 16 & CRQ 21
<p>Technical drawings for CQ 08 VG showing dimensions: 46, 18.5, PG 21, 15, 50.5, 34.</p>	<p>Technical drawings for CQ 08 C &amp; CQ 08 CA showing dimensions: 48, 28.7.</p>	<p>Technical drawings for CRQ 16 &amp; CRQ 21 showing dimensions: O, E, A, B, C, D, Ch.</p>

## Thermoplastic enclosures size “32.13”

**For use with all size “32.13” connector inserts.**

Characteristics of materials for CQ - MQ series.

In self-extinguishing grey RAL 7035 or jet black RAL 9005 thermoplastic material;  
gaskets in anti-aging, oil-resistant, grease-resistant and fuel-resistant NBR vinyl nitrile elastomer;  
with single-block locking lever in self-extinguishing thermoplastic material.



Male Inserts		Female Inserts	
<b>CQM 04/2</b> 4 Pin 40 amp + 2 Pin 10 amp (crimp)		<b>CQF 04/2</b> 4 Pin 40 amp + 2 Pin 10 amp (crimp)	
<b>CQM 08</b> 8 Pin 16 amp 500 volt (crimp)		<b>CQF 08</b> 8 Pin 16 amp 500 volt (crimp)	
<b>CQM 17</b> 17 Pin 10 amp 160 volt (crimp)		<b>CQF 17</b> 17 Pin 10 amp 160 volt (crimp)	

All dimensions in mm. For crimp pins refer to page 354.