

TECHNICAL DATA SHEET

PMA Divisible System - BLSGO Connection Splice

One-piece, IP40





Divisible connection splice ideal for retrofit and repairs

((

Applications:

• In industry, plant construction, machine building as well as in house and electrical installations

Features & Benefits:

- Easy installation and reopening if necessary
- · Conduit can be installed in fitting prior to closing
- · High conduit pull-out strength
- · High impact resistance
- Very good chemical properties
- Fits both conduit profiles fine (T) and coarse (G)

Ingress protection:

• IP40 (IEC EN 60529)

Materials:

• High-grade, specially formulated polyamide 6.6

Compatible with:

 PMA standard, slit and divisible conduits with standard nominal widths 10-23

Weathering resistance:

• Very good UV resistance and weathering characteristics

Colour:

Black

Chemical properties:


Please refer to www.pma.ch
(Technical Information / Chemical Resistance)

Environmental properties:

- Free from halogens and cadmium
- RoHS and REACH compliant

Product selection:								
Part no.	Cond	uit size	Dimensions in mm (nom.)		Weight	Packing unit		
black	NW (C)	NW (D)	A	В	kg/100 pcs	pcs/PU		
BLSGO-1010	10	10	36.0	16.0	0.3	10		
BLSGO-1212	12	12	35.5	19.5	0.4	10		
BLSGO-1717	17	17	38.5	25.0	0.5	10		
BLSGO-2323	23	23	39.0	31.5	0.8	10		

Our customer service dept. or local distribution partner will be pleased to help you concerning product availability and lead time



Thermal properties:	Value:	Test parameters:	Test method:
Temperature range	– 40+ 105 °C		PMA DO 9.21-4510
Short-term	+ 160 °C		

Content of delivery:

• Connection Splice

Assembly instructions:

- Lay in the conduit until the conduit stop, snap into place and lock the splice.
 - Please consider the appropriate assembly instructions on www.pma.ch