

Machine building and installation conduits and adapters

CF Easiflex

very flexible, medium



The PMA EASIFLEX conduit type CF are produced from specially modified polyamide (PA6). The material is self extinguishing and free of halogen, phosphor and cadmium. These economical, medium-wall conduits offer good impact resistance and flexibility. They are generally used in the machine building and installation industries. These conduits are generally available with fine profile.

Temperature range: – 40°C to +105°

Short term to: –140°C

System belonging to: PMA Economy Fittings, PMAFIX


Product performance: Meet requirements according to IEC EN 61386.



Order No. Black	Conduit size		Inside Diameter	Outside Diameter	stat.**/dyn. *** Radius	PU Meter
	NW	Metric				
CF - 07B	7	10	6.2 mm	10.0 mm	15 mm	50
CF - 10B	10	12	9.6 mm	13.0 mm	20 mm	50
CF - 12B	12	16	12.0 mm	15.8 mm	30 mm	50
CF - 17B	17	20	16.2 mm	21.2 mm	40 mm	50
CF - 23B	23	25	22.6 mm	28.5 mm	40 mm	50
CF - 29B	29	32	29.0 mm	34.5 mm	50 mm	50
CF - 36B	36	40	36.5 mm	42.5 mm	60 mm	30
CF - 48B	48	50	47.5 mm	54.5 mm	70 mm	30
CF - 70B	70	80	68.0 mm	80.0 mm	160 mm	30
CF - 95B	95	106	91.5 mm	105.5 mm	210 mm	30
SMART LINE						
LLPAG-56A	56	63	56.3mm	67.2mm	120mm	30

ALND

The Smart-Line connectors are generally used in the machine building, installation and construction industries.



Order No. IP66 Black	Thread metric	Fits to conduit size		Thread Length (g)	Overall Length (A)
		NW	metric		
ALND-M120	M12 x 1.5	10	12	11.0 mm	34.0 mm
ALND-M160	M16 x 1.5	10	12	11.0 mm	34.0 mm
ALND-M162	M16 x 1.5	12	16	11.0 mm	38.0 mm
ALND-M202	M20 x 1.5	12	16	11.0 mm	38.0 mm
ALND-M207	M20 x 1.5	17	20	11.0 mm	41.0 mm
ALND-M257	M25 x 1.5	17	20	12.0 mm	42.0 mm
ALND-M253	M12 x 1.5	23	25	12.0 mm	45.5 mm
ALND-M323	M32 x 1.5	23	25	15.0 mm	48.5 mm
ALND-M329	M32 x 1.5	29	32	15.0 mm	50.5 mm
ALND-M409	M40 x 1.5	29	32	19.0 mm	54.5 mm
ALND-M406	M40 x 1.5	36	40	19.0 mm	60.5 mm
ALND-M506	M50 x 1.5	36	40	19.0 mm	61.0 mm
ALND-M508	M50 x 1.5	48	50	19.0 mm	61.0 mm
ALND-M638	M63 x 1.5	48	50	19.0 mm	61.0 mm

- Specifically modified polyamide
- IP66 - One piece fitting with integral cone seal
- Self Extinguishing, free of halogen & cadmium
- Excellent impact strength

Temperature range: -40°C to +105°C:

Short Term: to +150°C

Content of Delivery: Fitting body with preinstalled retaining elements

