



ÖLFLEX® CRANE CF

Weather-resistant flat rubber cables with copper screening



Info

- For outdoor cable trolley application
- EMC-compliant



Benefits

- Weather-resistant for harsh environmental conditions
- Flat cables need less space than round cables
- Smaller bending radii is possible
- Copper braiding screens the cable against electromagnetic interference

Application range

- In crane systems on building sites and shipyards for fixed installation, or for flexible use in cable trolley systems
- Sewage treatment plants, steelworks and high rack facilities
- The application profiles for ÖLFLEX® CRANE and ÖLFLEX® LIFT cables can be found in the appendix, selection table A3

Product features

- Flame-retardant according IEC 60332-1-2

Norm references / Approvals

- Based on VDE 0250 (NGFLGÖU)

Product Make-up

- Strands of bare or tinned-copper wires
- Core insulation: rubber compound
- Individual core screening consist of
 - plastic foil wrapping
 - tin-plated copper braiding
 - plastic foil wrapping
- Outer sheath: special rubber compound

Technical data

	Classification ETIM 5.0 Class-ID: EC000825 ETIM 5.0 Class-Description: Flat cable
	Core identification code Up to 5 cores: colour-coded according to VDE 0293-308, refer to Appendix T9 From 6 cores: black with white numbers
	Conductor stranding Copper conductor according to VDE 0295/IEC 60228 up to 25 mm²: extra-fine wire, class 6 from 35 mm²: fine wire, class 5
	Minimum bending radius Flexible use: 10 x cable thickness Fixed installation: 4 x cable thickness
	Nominal voltage U ₀ /U: 300/500 V
	Test voltage 2000 V
	Protective conductor G = with GN-YE protective conductor X = without protective conductor
	Temperature range Flexible use: -25°C to +90°C Fixed installation: -40°C to +90°C

Article number	Number of cores and mm² per conductor	Outer dimensions, width x height (mm)	Copper index (kg/km)	Weight (kg/km)
ÖLFLEX® CRANE CF				
0041075	4 G 1.5	18.5 x 6.5	79	220
0041076	8 G 1.5	36.0 x 7.5	155	470
0041077	12 G 1.5	54.5 x 8.5	238	745
0041078	4 G 2.5	22.5 x 7.5	141	320
0041079	12 G 2.5	69.5 x 9.5	499	1180
0041080	4 G 4	29.0 x 10.5	219	505
0041081	4 G 6	31.0 x 10.5	302	605
0041082	4 G 10	36.0 x 11.5	472	840
0041083	4 G 16	41.5 x 13.5	687	1180
0041084	4 G 25	47.0 x 15.0	1114	1605
0041085	4 G 35	55.0 x 17.0	1482	2520
0041086	4 G 50	66.0 x 20.5	2238	3000

Unless specified otherwise, the shown product values are nominal values. Detailed values (e.g. tolerances) are available upon request.

Copper price basis: EUR 150/100 kg. Refer to catalogue appendix T17 for the definition and calculation of copper-related surcharges.

Please find our standard lengths at: www.lappkabel.de/en/cable-standardlengths

Packaging size: coil ≤ 30 kg or ≤ 250 m, otherwise drum

Please specify the preferred type of packaging (e.g. 1 x 500 m drum or 5 x 100 m coils).

Photographs are not to scale and do not represent detailed images of the respective products.

Similar products

- ÖLFLEX® CRANE F refer to page 170
- ÖLFLEX® LIFT F refer to page 172

Accessories

- Cable trolley systems
- Flat cable wedge clamps